



EXTRATECH 2001 (PTY) LTD

Member of the Redman Group

AGRICULTURAL EQUIPMENT

Brass Impact Sprinkler System



RAINMAN Impact Sprinklers

Brass Impact Sprinkler

Bearing:

Trajectory: 22 - 25 Degrees
Operating Range: 2.0 - 4.5 Bars
Flow Rate: .072 - 1.93 m³/H
Radius: 14.3 - 16.8 Meters

Features:

- Durable brass die-castings
- Stainless steel spring and fulcrum pin
- Chemical Resistant Washers
- 12 month warranty

Benefits:

- Drive arm runs on larger nozzles and high pressures
- Corrosion and grit resistant
- Manufactured to last



Nozzle Size

BARS @ Nozzle	3.57mm		3.97mm		4.36mm		4.76mm	
	Ø M	Flow (l/h)m ³	Ø M	Flow (l/h)m ³	Ø M	Flow (l/h)m ³	Ø M	Flow (l/h)m ³
2.0	14.3	0.720	14.8	0.880	15.3	1.070	14.8	1.260
2.5	14.3	0.760	14.8	0.990	15.3	1.210	14.8	1.410
3.0	14.8	0.810	14.8	1.080	15.3	1.310	14.8	1.560
3.5	14.8	0.870	14.8	1.180	16.3	1.420	15.8	1.680
4.0	14.8	0.910	15.8	1.250	17.3	1.520	16.3	1.790
4.5	16.3	1.080	17.3	1.310	18.3	1.510	16.8	1.930

Wetted Diameters – Radius in Meter ØM
Water Consumption (l/h) 1m³/hour – 1000L

The RAINMAN impact sprinkler is made of high quality brass to ensure a smooth operation and a long maintenance-free life. Available with 4 different nozzle sizes. The RAINMAN sprinkler is ideally suited for general agricultural irrigation including sugar cane, orchards, pastures, vegetables as well as parks and sports fields. Should the need arise spare parts are freely available.

RAINMAN Impact Sprinklers

Brass Impact Sprinkler - Parts

